

DS-2CC51A2P-DG1



Key Features

- Compact design
- CCD
- Auto white balance, auto gain control, electronic shutter control and backlight compensation
- Internal Synchronization
- 3-axis (pan/tilt/rotation) positioning allows adjustment for optimum Surveillance angles and position

Specification

Model	DS-2CC51A2P-DG1
Parameter	700TVL CCD Pinhole Camera
Camera	
Image Sensor	1/3" CCD
Signal System	PAL
Effective Pixels	976(H)×496(V)
Min. Illumination	0.1 Lux @ (F1.2,AGC ON)
Shutter speed	PAL: 1/50 s to 1/100,000 s
Lens	2.8mm, 3.6 mm(optional)
Lens Mount	M12
Day & Night	Electronic
Horizontal Resolution	700 TVL
Synchronization	Internal synchronization
Video Output	1Vp-p composite output (75 Ω/BNC)
S/N Ratio	More than 62 dB
General	
Working Temperature/Humidity	-30 °C - 60 °C (-22 °F - 140 °F) Humidity 90% or less (non-condensing)
Power Supply	12 V DC ± 10%
Power Consumption	Max. 2W
Dimensions	32.1×32.1×29.3 mm (1.26" × 1.26" × 1.15")
Weight	300 g (0.66 lbs)

Order Models

DS-2CC51A2P-DG1

Dimension

